

BIG Current Vandal Resistant Switch $\Phi 22\text{mm}$



Big range current:

3A 5A 8A 10A (15A) 16A 20A(21A)

Snap action, compact design, suit for small space

Variety Of Colors

Anti-Vandal IK09/ Sealed IP65


Illuminated and Non-Illuminated

Order Code

Series	Actuator Options	Terminal	Function	Current Voltage	Material Finish	Illuminated Options	Color	Color Voltage	Marking Current
L22B	F-Flat/blank	6.35X0.8(#250) quick connect terminal (T=0.8) blank	M- Momentary 1 1NO (SPST) 2 1NC (SPST) 3 1NO1NC (SPDT) Z- Latching 1 1NO (SPST) 2 1NC (SPST) 3 1NO1NC (SPDT)	02-2.5A 03-3A 05-5A 08-8A 10-10A 16-16A 21-21A D6-0.6A/ 125VDC D3-0.3A/ 250VDC	S- Stainless Steel	D-Dot R-Ring Non-Illuminated	W-White Y- Yellow B- Blue G- Green R- Red O- Orange	6V 12V 24V 36V 110V 230V	Custom Markings Available




Operation




Suggested Panel Cutout



Max. Panel Thickness:
Momentary Version: 0.315 (8.0)
Latching Version: 0.472 (12.0)



Illuminated





Technical Data




Type	L22B-F	L22B-F/R	L22B-F/D
Illuminated Options	Non-Illuminated	Ring	Dot
Terminal	PIN (6.35x0.8)		
Max. Switch Rating	3A 5A 8A 10A 15A(16A) 20A(21A)/ 250VAC, 125VAC 0.6A/ 125VDC 0.3A/ 250VDC		
Contact Resistance	$\leq 25\text{m}\Omega$		
Insulation Resistance	$\geq 100\text{M}\Omega$		
Dielectric Strength	Between non-consecutive terminals 1,000Vrms, 50/60Hz for 1min Between non-current carrying metal parts and each terminal 1,500Vrms, 50/60Hz for 1min Between ground and each terminal 1,500Vrms, 50/60Hz for 1min		
Shock resistance	Detraction: O.F.>0.5N: 1000m/s ² (approx. 100g) ON: 400m/s ² (approx. 40g) Malfunction: O.F.>0.5N: 200m/s ² (approx. 20g) OFF: 100m/s ² (approx. 10g)		
Vibration Resistance	10 - 50Hz, 1.5mm Double Amplitude		
Ambient Temp.	-25°C ~+85 °C		
Mechanical Life	2,000,000cycles		
Electrical Life	50,000cycles		
Contact Material	Silver Alloy		
Torque	5~14Nm		
Operation Pressure	10N		
Protection	IP65/ IK09		
Material			
Actuator	Stainless Steel		
Body	Stainless Steel		
Color			
Type	LED		
Voltage	6V/ 12V/ 24V/ 36V/ 110V/ 230V		
Color	R G Y O B W		
Life	Approx. 40, 000hours		

BIG Current Vandal Resistant SwitchΦ22mm


Terminal

	#250(t=0.8)	
Terminal type	Quick-connect terminal #187	Dimensions
Bottom common terminal		

Contact type

Common terminal types	SPDT	SPST-NC	常开式 SPST-NO
Bottom common terminal			

Dimension



MOMENTARY

LATCHING